

THE STRONGEST IN ITS CLASS!

HOLDER

NEW HOLDER S-SERIES

HOLDER S 100 | HOLDER S 115 | HOLDER S 130









VARIOUS APPLICATIONS:

WINTER MAINTENANCE

- Snow ploughing, blowing, sweeping, loading
- Cross-country ski-tracks
- Spreaders
- Brine spraying
- Ice scraping

MOWING AND GROUND CARE

- Mowing-suction combination
- Verge mowing
- Mowing (with rotary, wide area, cylinder and reach arm mower)
- Mulching
- Hedge cutting
- Watering

SWEEPING AND CLEANING

- Sweeper-suction combination
- Sweeping brush
- Removal and cleansing of road markings
- Cleansing of reflection posts and traffic signs
- Rubber removal
- Leaf removal
- Washing
- Synthetic turf cleaner
- Weed control (i.e. hot water)

TECHNICAL DATA

ENGINE	Deutz 4-cylinder 4-stroke turbo diesel , Tier-4-final, Stage-5-ready
Displacement	3621 cm³
Power	74.4 kW (102 HP) / 85 kW (115 HP) / 95 kW (128 HP)
Torque	302 lbf ft / 410 Nm
Rated speed	2200 rpm
Cooling	Water cooling
Fuel tank capacity	21.65 gal
DRIVE	Hydrostatic traction drive, controlled digital-electrically, stepless road speed control, Dual Drive, permanent four-wheel drive, four wheels of the same size
Maximum speed	25 mph
Brakes	Hydraulic operating brake on all four wheels, mechanical parking brake on the front axle with two drum brakes
HYDRAULICS	Hydraulic pump 11.1 gpm or on request tandem pump with adjustable flow divider 10.56 gpm + 6.6 gpm, variable displacement pump 0-31.68 gpm
Hydraulic oil quantity	7.92 gal
Lifting capacity	Front 5940 lb, CAT I, 3-dimensionally movable
Control valves	Up to 4 double-acting front valves and up to 3 double-acting rear valves
WEIGHT	Including driver at 165 lb, depending on tyres and equipment
Tare weight	approx. 6820 - 7590 lb
Permissible gross weight	12100 lb; optionally: 13200 lb
Permissible axle load	Front 7040 lb / rear 7040 lb
Tow-bar load on the trailer coupling	Max. 1760 lb
Towing capacity	Unbraked 5500 lb / overrun braked 9900 lb
Maximum payload	5280 lb / optionally: 6380 lb
DIMENSIONS	Depending on tyres
Wheelbase	71.93"
Total length	154.33"
Total height with cab	87.91" – 90.35"
Total outside width	52.36" – 62.20"
Turning circle inside /outside	76.38"/ 119.88"

HOLDER IN ACTION: www.youtube.com/user/maxholdergmbh



YOUR TOP ADVANTAGES

- High working hydraulic: simultaneous operation of two proportional functions, free set up of Joystick, 3 independent drives for attachments
- Mechanical front PTO and wheel stabilizer
- Improved agility (outer turning radius of 119.88")
- Three different seating options: one seat, two seats or one adjustable seat
- Touch display and LED lighting



NO COMPROMISES